



HYDROGEN EMISSIONS MEASUREMENT STUDY

A Collaborative Research Initiative of Environmental Defense Fund and Partners

Zero and low carbon hydrogen holds great promise as a decarbonization strategy. But to maximize its climate benefits, it is critical that it be produced, managed, and used in a way that minimizes emissions

Background

The universe's smallest molecule, hydrogen, is a leak-prone gas that causes climate warming. When released through venting, purging, or unintended leaks, it increases the concentrations of other greenhouses in the atmosphere (i.e. methane, tropospheric ozone and stratospheric water vapor). Like methane, hydrogen's warming effects are short lived, but potent: 34-40 times more powerful than carbon dioxide pound for pound over the first 20 years after its release. Recent studies indicate that if hydrogen emission rates are high, it can severely undermine the intended benefits of hydrogen deployment, particularly over the near term. The international hydrogen community, including the [US Department of Energy](#), [EU Joint Undertaking](#), [UK Department for Business Energy & Industrial Strategy](#), and the [International Energy Agency](#) have highlighted the importance of understanding hydrogen emissions, underscoring the need to monitor, measure, and mitigate leaks and releases.

What is not well understood is how much hydrogen is released from various processes and infrastructure types. Studies over the last 20 years suggest emission rate of 0.3-20% for components of the value chain, but this range is highly theoretical, because there are few empirical data on hydrogen emissions from real-world infrastructure. Current commercial technologies are designed to detect relatively high concentrations (at the parts-per-million level) as those can pose a safety risk. They do not detect the smaller "climate relevant" emissions – at the parts-per-billion level – and they lack the fast response necessary to

enable quantification of hydrogen plumes released from various infrastructure.

To responsibly deploy hydrogen at scale, across major industries, we need better understanding of hydrogen emission rates from representative facilities and equipment types. With the help of new hydrogen measurement technology and experts in making trace gas measurements, EDF is launching the first comprehensive Hydrogen Emissions Measurement Study in 2023.

Benefits of the Hydrogen Emissions Measurement Study

The study will quantify current emissions and improve hydrogen infrastructure development by:

- Establishing a baseline understanding of how much hydrogen is released and from where, thereby laying the foundation for best practices and mitigation strategies;
- Understanding emissions from existing infrastructure will aid demonstration projects, such as the Hydrogen Hubs, in the development of infrastructure with high environmental integrity;
- Offering insights into the effectiveness of current safety leak repair programs to minimize emissions, thereby supporting companies to establish operational excellence;
- Offering transparency and assurance of safety to local communities;

- Offering assurance to governments and private sector actors that investments in hydrogen will generate the promised climate benefits, backed by high-quality, directly measured data; and
- Saving valuable product by minimizing unintended hydrogen losses.

The study

EDF and partners seek industry leaders to join a collaborative study to quantify the hydrogen emission rate of various hydrogen infrastructure. The goal is to create a foundation of empirical data and knowledge that will inform management and decision making in hydrogen systems.

This study will involve making measurements at new and existing hydrogen infrastructure, using a prototype technology and scientifically rigorous methods designed by scientists who have decades of experience in emission measurements across sectors and geographies. Hydrogen facility types to be studied include fertilizer production, oil refining, methanol production, electrolysis, refueling, pipeline distribution, on-road transportation, storage, and others. The study aims to collect several data points for each facility type across multiple companies to get representative hydrogen emission rates.

Industry partners will have the opportunity to provide input into the measurement plan, review and help contextualize the findings, and participate in post-study communications. To ensure that companies have the freedom to fully participate, data will not be attributed to specific companies or locations, but instead will be aggregated and generalized. Results will be released as peer-reviewed scientific publications.

The detection technology

With Department of Energy funding, [Aerodyne Research](#) developed a prototype instrument capable of measuring hydrogen at a level of sensitivity and speed necessary to measure climate-relevant emission rates. The technology is based on optical principles and demonstrates a few seconds measurement precision of 50 ppb in situ. The first field testing took place in January 2023 at Colorado State University's METEC facility, with researchers from EDF, Cornell University, and CSU. Controlled-release experiments were carried out, including above- and under-ground releases of pure hydrogen gas and hydrogen/methane blended gas at various flow rates. The hydrogen sensor successfully detected small enhancement of hydrogen concentration downwind of the release point.

The emission quantification approaches

Two approaches will be used to quantify hydrogen emissions from concentration measurement: dual-tracer release and dispersion modeling. The dual-tracer approach involves releasing two trace gases at known rates at a facility that's emitting an unknown amount of hydrogen. Both tracers will be measured downwind along with hydrogen concentration, and then used as references to quantify

hydrogen emission rate. Common tracer gases include nitrous oxide and industrial acetylene, and can be adjusted based on the safety protocol onsite. The dispersion modeling approach will utilize wind and temperature measurements and an inversion model developed by scientists at Cornell University. Both approaches are scientifically robust and proven to quantify emissions with a high level of accuracy.

Timing

The study timeline is currently in development, with a start date in fall 2023.

In-kind contributions

The study is funded by philanthropic contributions to EDF. Companies will be asked to provide necessary staff time to ensure safe operations and facility access as in-kind contributions.

Partners

Aerodyne Research Inc., Cornell University, West Virginia University, Transport Energy Strategies, Colorado State University, National Renewable Energy Lab

Research team

Dr. Steven Hamburg, Chief Scientist, EDF

Dr. Tianyi Sun, Climate Scientist, EDF

Dr. David Nelson, President and CEO, Aerodyne Research, Inc.

Dr. Scott Herndon, Director of Atmospheric and Environmental Chemistry, Aerodyne Research, Inc.

Conner Daube, Manager of Field Measurement Studies, Aerodyne Research, Inc.

Dr. John Albertson, Professor of Civil and Environmental Engineering, Cornell University

Dr. Ahmad Momeni, Postdoctoral Research Associate, Civil and Environmental Engineering, Cornell University

Dr. Greeshma Gadikota, Assistant Professor and Croll Sesquicentennial Fellow in the School of Civil and Environmental Engineering, Cornell University

Dr. Nigel Clark, Energy Consultant, Transport Energy Strategies; Emeritus Professor at West Virginia University

Dr. Derek Johnson, Associate Professor of Mechanical and Aerospace Engineering, West Virginia University

David McKain, Consultant, Transport Energy Strategies

Environmental Defense Fund

For more information, contact:
Dr. Tianyi Sun, tsun@edf.org

T 212 505 2100

F 212 505 2375

[EDF.org](https://www.edf.org)

Environmental Defense Fund works around the world from offices in

New York / Washington / San Francisco / London / Beijing / La Paz, Mexico /

Brussels and other cities